

New and Improved QuickDip 14 or 28 gram kits

Made In Texas, by Texans

NOTE: This sheet must accompany bottle at all times.

Preparation:

The components are not flammable on their own, however once mixed the compound is very flammable. Do not use around open flame, do not smoke, and do not generate sparks.

Included in the package:

1. Instruction sheet, also found on my website here:
2. White polypropylene straight side re-sealable polypropylene jar containing the fuel mixture labeled as "QuickDip".
3. Small glass bottle labeled "binder".
4. Wooden stir sticks.
5. Small resalable plastic bag labeled "KNO₄", with a desiccant pack.

Here's how to mix it up.

Note:

Do not smoke or use spark-producing tools to avoid accidental ignition. Your tools can be wooden, stainless steel, brass or any other non-Ferris metal. I prefer the wooden stirs and stainless steel. Acetone is available at most hardware or Home Improvement stores, be sure to read the label warnings on the use of acetone. Be sure to use 100% Acetone and no substitutes, also fingernail polish remover will not work.

1. Empty the bottle of binder into the jar. When empty fill the bottle about half full of fresh acetone, shake well and pour this into the white jar as well.
2. Now add 1 teaspoon of acetone to the 14 gram kit and the 28 gram kit will need 2, of clean fresh acetone. Stir well, you will get a viscous black/gray slurry that is one uniform color.
3. NOTE: Never add oxidizer to a dry mix, the possibility of accidental ignition would increase dramatically.
4. Open the zip lock bag of Oxidizer then carefully remove the desiccant pack and dispose of properly.
5. Next you will add the Oxidizer to the wet fuel mix. Pour all of it in and stir well. It will be thick and may require some acetone to thin, you can't add too much acetone. We're only trying to thin the mix enough to mix the components thoroughly. We will address dipping viscosity later. We want it wet enough to stir, the compound should not cling to the stir stick.
6. Stir well. The fuel and the oxidizer do not dissolve in the acetone; they need to be suspended in the mix.
7. If you need to thicken the mix stir while blowing over the top of the jar to flash the acetone off. This will allow you to reach the desired viscosity. If you need to thin, add acetone in small amounts. Always stir well.
8. I like to keep the dip about the consistency of latex paint. When the viscosity is right it will not drip off the stir stick. It will cling.
9. The proper viscosity is very hard to describe in text. What you're looking for is a mix that will cling to the Hot Wire Coil of your igniter assembly. You will size your starters according to your needs. Some motors will require a thin starter and some will require a much thicker starter.
10. A thin igniter may require a single dip over a single strand of resistance wrapped wire. Thinner Starters may require a coat of fingernail polish to make them more robust. A thicker igniter can be made by multiple dips or folding your hot wire coil over. I frequently use doubled coils or even triple folds.

11. Dip your hot wire assembly until you reach the desired length and OD. Let dry overnight.
12. If your mix dries out in storage you can re-constitute it by adding more acetone. Acetone is Hygroscopic, use fresh acetone or acetone that has been kept well sealed for the best results. Use 100% Acetone only. FYI Your wife's fingernail polish remover will not work.

Please note: When you purchase this or any other item from QuickBurst you are stating that you have read, understand and agree to The Manufacturers Intended Use as follows, The manufacturers intended use of QuickDip is for use in Model or Amateur rocket projects. Any use other than the manufacturers intended use is outside of the manufacturers intentioned use.

Making Motor Starters,

This is so simple that after you have done it a few times you will be an expert. Just follow the steps described below.

Step 1. (Shooter wire or other twin conductor)

Separate the two conductors. Cut one lead about 1/2 to 5/8" below the other. Do not cut or damage the other lead while doing this.

Step 2

Strip about 1/4" insulation off each lead and bend the long lead out of the way.

Step 3

Secure one end of the nichrome wire with your thumbnail and wrap the nichrome around the exposed copper about three or four wraps. Now bend the remaining copper over and down, crimping the nichrome in place.

Step 4

Wrap the nichrome barber pole style up the long lead over the insulation. Four wraps are plenty. Crimp as in Step 3 and cut excess nichrome.

Step 5

Thin or smaller starters will require a coat of fingernail polish, to make them much more robust.
Finished.

Now mix your QuickDip and dip away. The dip can be layered if needed. Try to keep coating between 1/16" and 1/8" for best results. If a thicker starter is required fold your coil down and against the lead wire then dip. Another great use is to paint the top portion of the upper grain in reloadable motors.

Contact Info

Email: info@quickburst.net

Phone: 979-373-6601

NOTES:

I prefer to use shooter wire or lampcord to make my igniters, it can also be done easily with 24 AWG Cat 5. I've found that 32 AWG nichrome 80 resistance wire works for any general purpose ground start igniter. Airstarts and Clusters will take a bit of research on your part, for these I typically use the 34 or the 36 AWG Nichrome 80

Always Bench Test, to be sure.

David Bachelder

Need Supplies?

www.quickburst.net

Cell Phone: 979-373-6601